



all solutions in one partner®

SCHEMA TECNICA - CODICE NF57



NF57 - VITE AUTOFILETTANTE FOSFATATA NERA DOPPIO FILETTO/DOPPIA PUNTA -

DESCRIZIONE PRODOTTO

Vite fosfatata da cartongesso per fissaggio lastre-lamiera con eccezionale tempo di perforazione medio per la vite 3.5x25 di 0,375 sec.

Le misure 3.5x25 e 3.5x35 possono essere fornite anche in buste o in barattoli da 1000 pz o rispettivamente da 7000 e 5000 pz.

Inoltre per i codici NF57002, NF57003 e NF57004 è possibile fornire la confezione personalizzata con il nome ed il logo del cliente.

La stessa vite nastrata crea il codice NF59.



INFORMAZIONI TECNICHE

Codice	Descrizione
NF57001	Vite autofilettante fosfatata nera Ø3,5x19mm
NF57002JY	Vite autofilettante fosfatata nera Ø3,5x25mm
NF57002P	Vite autofilettante fosfatata nera Ø3,5x25mm personalizzata
NF57016	Vite autofilettante fosfatata nera Ø3,5x25mm
NF57000	Vite autofilettante fosfatata nera Ø3,5x30mm
NF57003JY	Vite autofilettante fosfatata nera Ø3,5x35mm
NF57003P	Vite autofilettante fosfatata nera Ø3,5x35mm personalizzata
NF57017	Vite autofilettante fosfatata nera Ø3,5x35mm
NF57004JY	Vite autofilettante fosfatata nera Ø3,5x45mm
NF57004P	Vite autofilettante fosfatata nera Ø3,5x45mm personalizzata
NF57018	Vite autofilettante fosfatata nera Ø3,5x45mm
NF57005JY	Vite autofilettante fosfatata nera Ø3,5x55mm
NF57019	Vite autofilettante fosfatata nera Ø3,5x55mm
NF57006	Vite autofilettante fosfatata nera Ø4,2x70mm
NF57007	Vite autofilettante fosfatata nera Ø4,2x80mm
NF57008	Vite autofilettante fosfatata nera Ø4,8x90mm
NF57009	Vite autofilettante fosfatata nera Ø4,8x100mm



all solutions in one partner®

SCHEMA TECNICA - CODICE NF57



INFORMAZIONI TECNICHE

Codice	Descrizione
NF57010	Vite autofilettante fosfatata nera Ø4,8x110mm
NF57011	Vite autofilettante fosfatata nera Ø4,8x120mm
NF57012	Vite autofilettante fosfatata nera Ø4,8x130mm
NF57013	Vite autofilettante fosfatata nera Ø4,8x140mm
NF57014	Vite autofilettante fosfatata nera Ø4,8x150mm
NF57015	Vite autofilettante fosfatata nera Ø4,8x160mm
NF57016	Vite autofilettante fosfatata nera Ø3,5x25mm
NF57017	Vite autofilettante fosfatata nera Ø3,5x35mm

VALORI DI ESTRAZIONE

Codice	Resistenza allo strappo su lamiera 6/10		Resistenza garantita allo strappo su lamiera 6/10	
	kgf	kN	kgf	kN
NF57001	208	2.08	104	1.04
NF57002JY	208	2.08	104	1.04
NF57002P	208	2.08	104	1.04
NF57016	208	2.08	104	1.04
NF57000	208	2.08	104	1.04
NF57003JY	208	2.08	104	1.04
NF57003P	208	2.08	104	1.04
NF57017	208	2.08	104	1.04
NF57004JY	208	2.08	104	1.04
NF57004P	208	2.08	104	1.04
NF57018	208	2.08	104	1.04
NF57005JY	208	2.08	104	1.04
NF57019	208	2.08	104	1.04
NF57006	208	2.08	104	1.04
NF57007	208	2.08	104	1.04
NF57008	208	2.08	104	1.04
NF57009	208	2.08	104	1.04
NF57010	208	2.08	104	1.04
NF57011	208	2.08	104	1.04
NF57012	208	2.08	104	1.04
NF57013	208	2.08	104	1.04
NF57014	208	2.08	104	1.04
NF57015	208	2.08	104	1.04
NF57016	208	2.08	104	1.04
NF57017	208	2.08	104	1.04

Coefficiente di sicurezza adottato: 2



all solutions in one partner®

SCHEMA TECNICA - CODICE NF57



VALORI DI RESISTENZA A TAGLIO

Codice	Resistenza a taglio su lamiera 6/10		Resistenza garantita a taglio su lamiera 6/10	
	kgf	kN	kgf	kN
NF57001	240	2.40	120	1.20
NF57002JY	240	2.40	120	1.20
NF57002P	240	2.40	120	1.20
NF57016	240	2.40	120	1.20
NF57000	240	2.40	120	1.20
NF57003JY	240	2.40	120	1.20
NF57003P	240	2.40	120	1.20
NF57017	240	2.40	120	1.20
NF57004JY	254	2.54	127	1.27
NF57004P	254	2.54	127	1.27
NF57018	254	2.54	127	1.27
NF57005JY	264	2.64	132	1.32
NF57019	264	2.64	132	1.32
NF57006	260	2.60	130	1.30
NF57007	260	2.60	130	1.30
NF57008	260	2.60	130	1.30
NF57009	264	2.64	132	1.32
NF57010	240	2.40	120	1.20
NF57011	240	2.40	120	1.20
NF57012	240	2.40	120	1.20
NF57013	240	2.40	120	1.20
NF57014	240	2.40	120	1.20
NF57015	240	2.40	120	1.20
NF57016	240	2.40	120	1.20
NF57017	240	2.40	120	1.20

Coefficiente di sicurezza adottato: 2



all solutions in one partner®

DATA SHEET - CODE NF57



NF57 - BLACK PHOSPHATED SELF-TAPPING SCREW DOUBLE THREAD/

PRODUCT DESCRIPTION

Phosphated plasterboard screw for sheet-laminate fixing with an outstanding average drilling time for the 3.5x25 screw of 0.375 sec.

The 3.5x25 and 3.5x35 sizes can also be supplied in bags or in cans of 1000 pcs. or 7000 and 5000 pcs. respectively.

In addition, for codes NF57002, NF57003 and NF57004, customised packaging with the customer's name and logo can be supplied.

The same taped screw creates the code NF59.



TECHNICAL INFORMATION

Code	Description
NF57001	Black phosphated self-tapping screw Ø3,5x19mm
NF57002JY	Black phosphated self-tapping screw Ø3,5x25mm
NF57002P	Black phosphated self-tapping screw Ø3,5x25mm personalised
NF57016	Black phosphated self-tapping screw Ø3,5x25mm
NF57000	Black phosphated self-tapping screw Ø3,5x30mm
NF57003JY	Black phosphated self-tapping screw Ø3,5x35mm
NF57003P	Black phosphated self-tapping screw Ø3,5x35mm personalised
NF57017	Black phosphated self-tapping screw Ø3,5x35mm
NF57004JY	Black phosphated self-tapping screw Ø3,5x45mm
NF57004P	Black phosphated self-tapping screw Ø3,5x45mm personalised
NF57018	Black phosphated self-tapping screw Ø3,5x45mm
NF57005JY	Black phosphated self-tapping screw Ø3,5x55mm
NF57019	Black phosphated self-tapping screw Ø3,5x55mm
NF57006	Black phosphated self-tapping screw Ø4,2x70mm
NF57007	Black phosphated self-tapping screw Ø4,2x80mm
NF57008	Black phosphated self-tapping screw Ø4,8x90mm
NF57009	Black phosphated self-tapping screw Ø4,8x100mm



all solutions in one partner®

DATA SHEET - CODE NF57



TECHNICAL INFORMATION

Code	Description
NF57010	Black phosphated self-tapping screw Ø4,8x110mm
NF57011	Black phosphated self-tapping screw Ø4,8x120mm
NF57012	Black phosphated self-tapping screw Ø4,8x130mm
NF57013	Black phosphated self-tapping screw Ø4,8x140mm
NF57014	Black phosphated self-tapping screw Ø4,8x150mm
NF57015	Black phosphated self-tapping screw Ø4,8x160mm
NF57016	Black phosphated self-tapping screw Ø3,5x25mm
NF57017	Black phosphated self-tapping screw Ø3,5x35mm

EXTRACTION VALUES

Code	Tear resistance on sheet metal 6/10		Guaranteed tear resistance on sheet metal 6/10	
	kgf	kN	kgf	kN
NF57001	208	2.08	104	1.04
NF57002JY	208	2.08	104	1.04
NF57002P	208	2.08	104	1.04
NF57016	208	2.08	104	1.04
NF57000	208	2.08	104	1.04
NF57003JY	208	2.08	104	1.04
NF57003P	208	2.08	104	1.04
NF57017	208	2.08	104	1.04
NF57004JY	208	2.08	104	1.04
NF57004P	208	2.08	104	1.04
NF57018	208	2.08	104	1.04
NF57005JY	208	2.08	104	1.04
NF57019	208	2.08	104	1.04
NF57006	208	2.08	104	1.04
NF57007	208	2.08	104	1.04
NF57008	208	2.08	104	1.04
NF57009	208	2.08	104	1.04
NF57010	208	2.08	104	1.04
NF57011	208	2.08	104	1.04
NF57012	208	2.08	104	1.04
NF57013	208	2.08	104	1.04
NF57014	208	2.08	104	1.04
NF57015	208	2.08	104	1.04
NF57016	208	2.08	104	1.04
NF57017	208	2.08	104	1.04

Safety factor adopted: 2



all solutions in one partner®

DATA SHEET - CODE NF57



SHEAR STRENGTH VALUES

Code	Shear resistance on sheet metal 6/10		Guaranteed shear strength on sheet metal 6/10	
	kgf	kN	kgf	kN
NF57001	240	2.40	120	1.20
NF57002JY	240	2.40	120	1.20
NF57002P	240	2.40	120	1.20
NF57016	240	2.40	120	1.20
NF57000	240	2.40	120	1.20
NF57003JY	240	2.40	120	1.20
NF57003P	240	2.40	120	1.20
NF57017	240	2.40	120	1.20
NF57004JY	254	2.54	127	1.27
NF57004P	254	2.54	127	1.27
NF57018	254	2.54	127	1.27
NF57005JY	264	2.64	132	1.32
NF57019	264	2.64	132	1.32
NF57006	260	2.60	130	1.30
NF57007	260	2.60	130	1.30
NF57008	260	2.60	130	1.30
NF57009	264	2.64	132	1.32
NF57010	240	2.40	120	1.20
NF57011	240	2.40	120	1.20
NF57012	240	2.40	120	1.20
NF57013	240	2.40	120	1.20
NF57014	240	2.40	120	1.20
NF57015	240	2.40	120	1.20
NF57016	240	2.40	120	1.20
NF57017	240	2.40	120	1.20

Safety factor adopted: 2